

Nazwa tkaniny	kolor	gramatura	kurczliwość	odporność koloru	Skład					
RZP1001	Złamana biel	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZP1002	Srebrzysty popiel	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZP1003	Beżowe cappucino	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZP1004	Szara czerń	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZP1005	Piaskowy beż	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZP1006	Szary oliwkowy	180	1%	5	85% pes, 15% pu	40	**	x	x	x
RZL100	Prążkowana biel	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL200	Prążkowany ecru	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL300	Prążkowany szary	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL400	Prążkowany grafit	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL500	Prążkowany róż	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL600	Prążkowany błękit	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZL700	Prążkowany granat	200	1%	4	42% pes, 58% co	40	*	x	P	x
RZMA1	Przejrzysta czerń	95	3%	5	100% pes	30	**	x	P	x
RZMA2	Przejrzysty popiel	95	3%	5	100% pes	30	**	x	P	x
RZMA3	Przejrzysty beż	95	3%	5	100% pes	30	**	x	P	x
RZMA4	Przejrzysty ecru	95	3%	5	100% pes	30	**	x	P	x
RZMAL1	Halkowa biel	50	3%	5	100% pes	40	*	x	P	x
RZN501	Tiulowa biel	55	1%	4	79% pes, 21% vi	30	*	x	P	x
RZN502	Tiulowa brudna biel	55	1%	4	79% pes, 21% vi	30	*	x	P	x
RZN503	Tiulowy szary	55	1%	4	79% pes, 21% vi	30	*	x	P	x
RZN504	Tiulowy róż	55	1%	4	79% pes, 21% vi	30	*	x	P	x
RZN505	Tiulowy błękit	55	1%	4	79% pes, 21% vi	30	*	x	P	x